

TECHNICAL DATA

PROPERTIES	LYT-PCM800	LYT-PCM800SP	REFERENCE
Color	Grey	Grey	Visual
Density[g/cc]	2.5	2.5[Solvent-contained]	ASTM D792
Temperature range	-40~125	-40~125	
Modulus	8.0	8.0	ASTM D 5045
Modulus	0.012	0.012	ASTM D 5045
Modulus	0.007	0.007	ASTM D 5045
Modulus	$>4 \times 10^{13}$	$>4 \times 10^{13}$	ASTM D2583
Dielectric constant [@1kHz/1MHz]	> 10	> 10	ASTM D1505
Flammability	V-0	V-0	UL94

Note: The data indicated above are all typical test values, the results are for reference only, and can not be used as the product performance.

ATTENTION

- Do not eat
- Keep out of the reach of children
- Keep the product away from fire
- Please confirm the correctness before use
- Please make sure the product surface is clean

STORAGE AND SHELF LIFE

The product needs to be sealed and stored in Temperature range: 15~35 and Relative humidity does not exceed 65%
Storage Validity: 12 Months from the date of packing.

HOW TO ORDER

LYT-PCM800 Products are shipped in sheet or roll form, and can also be die-cut in special shapes according to customer needs.
LYT-PCM800SP Products are shipped in 300cc Aluminium tubes , 1Kg Canned pack.